

<p>{tab=???????? ?????????????}</p> <table border="0" cellspacing="10" cellpadding="0" style="width: 615px; background-color: #ffffff;"> <tr> <td valign="top"> <p style="font-family: arial; font-size: 12px;"></p> </td> <td> <p style="text-align: left;"></p> <p style="font-family: arial, helvetica, sans-serif; font-size: 10pt; line-height: 21px; color: #777777;">?? BF2E1 ?????? ??? PRI / ISDN module ??? ?? Gateways ??? ??? ?????? berofix.
To BF2E1 module ?????? ?? ?????????? ?????????? ?? NT (????????????? ??? ??????????) ? TE (????????????? ??????????????) ?????????????? ? ?????????????? Pin-Out ?????? ??? ?????????? ?????? ?????? ?? ?????????????? ?????????????????????? ?? PINS 1,2,4,5. ?? ??????? ?? ?????????????????????? ??? ?????????? NT-mode ??????? ?? ?????????????? ??? ♦cross ?????????", ?? ?????? ?????? ?????????????? ?????????????? (BFE1Cross). ??????? ?????????????? (120/75 omhs) ?????? ?????????????? ??? ?????? DIP ?????????????? ??? module.</p></td> </tr> </table> <p>{tab=????????????????}</p> <table border="0" cellspacing="10" cellpadding="0" style="width: 615px; background-color: #ffffff;"> <tr> <td align="center" style="width: 150px;"> <p style="font-family: arial; font-size: 12px;"></p> </td> <td align="center" style="width: 150px;"></td> <td align="center"></td> </tr> </table> <p>{tab=????????????????}</p> <table border="0" cellspacing="10" cellpadding="0" style="width: 615px; background-color: #ffffff;"> <tr> <td style="font-family: Arial, Helvetica, sans-serif; font-size: 10pt;"> <p style="font-family: arial; font-size: 12px;">?????????????????</p> <ul style="font-family: arial, helvetica, sans-serif; font-size: 10pt; color: #777777;"> <li style="font-family: arial; font-size: 12px;">2 PRI (S2M) Port <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">Each Port configurable as NT or TE <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">Termination Resistors 120 ohm switchable via DIPs <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">Layer 2 is Q.921 and Layer 3 is Q.931 (EuroISDN DSS1) compatible <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">DSS1 Feature set: CLIP/No-Screening, CLIR, COLP, UUS, MCID, CD, CNIP <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">Q.SIG feature set: CNIP <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">?????????????: 105 x 46 x 9 mm <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">??????? : < 40g <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">Operating Temperature: 0-70♦C <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">CE and TBR-4 compliance (ISDN PRI) <p style="font-family: arial; font-size: 12px;">
</p> <span style="text-align:

left; color: #bb0000;"]>? Datasheet moduls</td> </tr>
</table> <p>{tab= Accessories}</p> <table border="0" cellspacing="10" cellpadding="0" style="width: 615px;"]> <tr> <td> <p style="font-family: arial; font-size: 12px;"]>Accessories</p> <ul style="font-family: arial, helvetica, sans-serif; font-size: 10pt; color: #777777;"]> <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; margin-top: 0px; margin-right: 0px; margin-bottom: 0px; border-width: 0px;"]>BFBridge (to use all 4 RJ45 slots on a Baseboard with one bf4S0,bf4FXS,bf4FXO,bf2S02FXS) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;"]>BFTAdapters (to connect 2 BRI or analog Lines on one RJ45 of the berofix) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;"]>BFPCM (PCM Cable to interconnect berofix Baseboards) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;"]>BFE1Cross, (1.8m E1/T1 "cross-over" cable) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;"]>BF19bracket (19 inch rack mount bracket for berofix Boxes) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;"]>BFANTS (small 7 cm stock antenna for BF2GSM modules) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;"]>BFANTL (2m cable antenna with magnetic foot for BF2GSM modules) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;"]>BFFXXCable (RJ45 to RJ11 cable to use with berofix analog modules) <p style="font-family: arial; font-size: 12px;"]>
</p> </td> </tr> </table> <p>{/tabs}</p>