

beroNet Telephony Appliance



19" 1U Rack Mountable



€ 879,00

(excl. Shipping & VAT)
Minus your Partner Discount

Compatible with:



- No moving parts, long-life and reliable
- 100% Aluminium construction, Robust, Lightweight and Rust-Free
- There is a module for every Scenario - PRI, BRI, Hybrid, Analog & GSM
- Install any Operating System on the same Appliance
- PCM connector extends your Appliance with an additional beroNet Gateway
- Remotely manage and monitor connectivity through beroNet Cloud
- Operational use of under 24W saving €200 per year in electricity
- Silent & can be placed anywhere in any office
- GSM ready for Least Cost Routing & Mobile PBX
- SkypeConnect™ integrates Skype into the PBX installation

Green Tech 20% ROI/Year	100% Silent 	GSM Ready 	Solid State 	Tough
Modular 	Any OS 	Extensible 	Cloud Managed 	Skype Connect

Technical Details

Hardware:

- Intel Atom N2800 2x1,86Ghz
- 2GB RAM
- 30 GB SSD
- 4 x external USB 2.0, Gigabit Ethernet port
- Keyboard and Monitor Support
- Silent system and Fanless design

Telephony:

The beronet Telephony Appliance is available in 3 different versions depending on the channel density and amount of module slots

- "SBE" Edition for up-to 16 concurrent channels and one module slot for one of the following modules:
 - BF2S02FXS 2 ISDN BRI and 2 analog FXS ports
 - BF4FXO 4 analog FXO ports
 - BF4FXS 4 analog FXS ports
- "16" and "64" Channel Edition for up-to 16 or 64 concurrent channels with two module slots for up to two of the following modules:
 - BF4S0 4 ISDN BRI ports
 - BF2S02FXS 2 ISDN BRI and 2 analog FXS ports
 - BF1E1 1 ISDN PRI /E1 ports
 - BF2E1 2 ISDN PRI/E1 ports
 - BF4FXO 4 analog FXO ports
 - BF4FXS 4 analog FXS ports
 - BF2GSM 2 GSM ports

Dimensions and Weight:

- Dimensions: 35 x 25,5 x 4,6 cm
- Mounting: 1U industry with optional 19" Brackets or wallmountable chassis
- weight: 2 kg (*depending on module configuration*)
- Power supply: 110-230V operating 12V DC at 3A

Environment:

- Storage Temperature: -20° to 70°C
- Operating Temperature: 0° to 40°C
- Humidity: 20% - 95%, non-condensing