{tab=??????? ???????????} <table border="0" cellspacing="10" cellpadding="0" style="width: 615px; background-color: #ffffff;"> <tr> <td valign="top"> </td> <td> ?? BF2E1 ????? ??? PRI / ISDN module ??? ?? Gateways ??? ??? ?????? berofix.
To BF2E1 module ?????? ?? ????????? ??????? ?? NT (??????????? ??? ???????) ? TE (?????????? ??????????) ??????????. ? ?????????? Pin-Out ????? ??? ???????? ????? ????? ?? ?????????? ?????????????? ?? PINS 1,2,4,5. ?? ?????? ?? ?????????????? ??? ???????? NT-mode ?????? ?? ????????? ??? ?cross ???????", ?? ????? ????? ????????? ??????????? (BFE1Cross). ?????? ??????????? (120/75 omhs) ????? ????????? ??? ???? DIP ????????? ??? module. </td> </tr> </table> {tab=???????????} <table border="0" cellspacing="10" cellpadding="0" style="width: 615px; background-color: #ffffff;"> <tr> <td align="center" style="width: 150px;"> </td> <td align="center" style="width: 150px;"> </td> <td align="center"></td> </tr> </table> {tab=????????????} <table border="0" cellspacing="10" cellpadding="0" style="width: 615px; background-color: #ffffff;"> <tr> <td style="font-family: Arial, Helvetica, sans-serif; font-size: 10pt;"> ????????????: <ul style="font-family: arial, helvetica, sans-serif; font-size: 10pt; color: #777777;"> <li style="font-family: arial; font-size: 12px;">2 PRI (S2M) Port <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">Each Port configurable as NT or TE <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">Termination Resistors 120 ohm switchable via DIPs <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">Layer 2 is Q.921 and Layer 3 is Q.931 (EuroISDN DSS1) compatible <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">DSS1 Feature set: CLIP/No-Screening, CLIR, COLP, UUS, MCID, CD, CNIP <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">Q.SIG feature set: CNIP <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">???????????: 105 x 46 x 9 mm <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">?????: < 40g <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">Operating Temperature: 0-70&#65533;C <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">CE and TBR-4 compliance (ISDN PRI)
 <span style="text-align:

left; color: #bb0000;">? Datasheet moduls</td> </tr> </table> {tab= Accessories} <table border="0" cellspacing="10" cellpadding="0" style="width: 615px;"> <tr> <td> Accessories <ul style="font-family: arial, helvetica, sans-serif; font-size: 10pt; color: #777777;"> <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; margin-top: 0px; margin-right: 0px; margin-bottom: 0px; border-width: 0px;">BFBridge (to use all 4 RJ45 slots on a Baseboard with one bf4S0,bf4FXS,bf4FXO,bf2S02FXS) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">BFTAdapters (to connect 2 BRI or analog Lines on one RJ45 of the berofix) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">BFPCM (PCM Cable to interconnect berofix Baseboards) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">BFE1Cross, (1.8m E1/T1 "cross-over" cable) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">BF19bracket (19 inch rack mount bracket for berofix Boxes) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">BFANTS (small 7 cm stock antenna for BF2GSM modules) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">BFANTL (2m cable antenna with magnetic foot for BF2GSM modules) <li style="padding-top: 0px; padding-right: 0px; padding-bottom: 0px; border-style: initial; border-color: initial; border-width: 0px; margin: 0px;">BFFXXCable (RJ45 to RJ11 cable to use with berofix analog modules)
 </td> </tr> </table> {/tabs}